

## SAFETY DATA SHEET

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 453/2010

## 1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name NEOASTRA DGC – HYDROCARBON BASED DAYLIGHT

FLUORESCENT INK CONCENTRATE

CAS No. Mixture.
EINECS No. Mixture.
REACH Registration No. None assigned.

1.2 Relevant identified uses of the substance or

mixture and uses advised against

Identified use(s) For use in the Magnetic Particle Inspection Process (BS EN

ISO 9934-2). Dilution rate 50:1 with a suitable

hydrocarbon carrier.

Uses advised against None known.

1.3 Details of the supplier of the Safety Data Sheet

Company Identification Johnson and Allen Ltd.

Neocol Works Smithfield Sheffield S3 7AR. 0114 2738066

 Telephone
 0114 2738066

 Fax
 0114 2729842

 E-mail
 info@johnsonandallen.co.uk

1.4 Emergency telephone number

Emergency Phone No. 0114 2738066 (UK office hours 08.30-17.00)

### 2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

**2.1.1 Regulation (EC) No. 1272/2008 (CLP)** Asp. Tox. 1; May be fatal if swallowed and enters airways.

Repeated exposure may cause skin dryness or cracking.

**2.1.2 Directive 67/548/EEC & Directive 1999/45/EC** Xn; Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking.

2.2 Label elements

2.2.1 Label elements According to Regulation (EC) No. 1272/2008 (CLP)

Product Name NEOASTRA DGC – HYDROCARBON BASED DAYLIGHT

FLUORESCENT INK CONCENTRATE

Hazard Pictogram

GHS08

Signal word(s) Danger.

Hazard statement(s) H304: May be fatal if swallowed and enters airways.

EUH066: Repeated exposure may cause skin dryness or

cracking.

Revision: 2.1 Page: 1/8 Date: 19/02/2020



Precautionary statement(s) P301 + P310: IF SWALLOWED: Immediately call a POISON

CENTRE or doctor/physician. P331: Do NOT induce vomiting.

P405: Store locked up.

P501: Dispose of contents/container to: Licensed recycler.

2.2.2 Label elements According to Directive 67/548/EEC & Directive 1999/45/EC Product Name

NEOASTRA DGC - HYDROCARBON BASED DAYLIGHT

FLUORESCENT INK CONCENTRATE

Risk Phrases R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

S2, S23, S24, S62

2.3 Other hazards None.

2.4 **Additional Information** For full text of H/P phrases see section 16.

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Mixtures

EC Classification No. 1272/2008

Hazard Symbol

Safety Phrases

Hazardous ingredient(s)	%W/W	CAS No.	EC No.	REACH	Hazard pictogram(s) and
				Registration No.	Hazard statement(s)
Distillates (petroleum),	>90	64742-47-8	265-149-8	01-2119453414-	GHS08, Asp. Tox. 1;
hydrotreated light;				43-0001	H304, EUH066
Kerosine — unspecified					

## EC Classification No. 67/548/EEC

Hazardous ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	EC Classification and Risk Phrases
Distillates (petroleum),	>90	64742-47-8	265-149-8	01-2119453414-	Xn; R65, R66
hydrotreated light;				43-0001	
Kerosine — unspecified					

## 3.2 Additional Information

For full text of H/P phrases see section 16.

Date: 19/02/2020 Revision: 2.1 Page: 2/8



## 4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation If breathing is difficult, remove victim to fresh air and keep at

rest in a position comfortable for breathing. If symptoms

persist, obtain medical attention.

Skin Contact

Wash with plenty of soap and wa

Wash with plenty of soap and water. Remove contaminated

clothing and wash clothing before reuse. If symptoms persist,

obtain medical attention.

Eye Contact

Flush eyes with water for at least 15 minutes while holding eyelids open. If symptoms persist, obtain medical attention.

IF SWALLOWED: Do NOT induce vomiting. Immediately call a

POISON CENTRE or doctor/physician.

4.2 Most important symptoms and effects, both

acute and delayed

Ingestion

Aspiration into the lungs may cause chemical pneumonitis, which can be fatal. Repeated exposure may cause skin

dryness or cracking.

4.3 Indication of any immediate medical attention

and special treatment needed

Unlikely to be required but if necessary treat symptomatically.

### 5. SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing Media

Suitable Extinguishing Media Extinguish with carbon dioxide, dry chemical, foam or

waterspray.

Unsuitable Extinguishing Media

None known.

5.2 Special hazards arising from the substance or

mixture

Decomposes in a fire giving off toxic fumes: Carbon

monoxide, Carbon dioxide.

5.3 Advice for fire-fighters Fire fighters should wear complete protective clothing

including self-contained breathing apparatus. Keep containers

cool by spraying with water if exposed to fire.

#### 6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation. Avoid inhalation of high concentrations of vapours. Wear suitable protective clothing, gloves and eye/face protection.

6.2 Environmental precautions

6.4

6.3 Methods and material for containment and

cleaning up

Reference to other sections

Do not allow to enter drains, sewers or watercourses.

Adsorb spillages onto sand, earth or any suitable adsorbent

material. Transfer to a container for disposal.

See Also Section 8, 13.

Revision: 2.1 Page: 3/8 Date: 19/02/2020



## 7. SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling Provide adequate ventilation. Avoid inhalation of high

> concentrations of vapours. Avoid prolonged skin contact. Wear suitable protective clothing, gloves and eye/face protection. Wash thoroughly with soap and water after handling. Do not eat, drink or smoke during work.

7.2 Conditions for safe storage, including any

incompatibilities

Storage Temperature

Storage Life

Incompatible materials

Ambient. Keep at temperature not exceeding (°C): 50°C. Stable under normal conditions. Recommended: 3 Year(s). Strong oxidising agents, Natural rubber, Polystyrene, Butyl

rubber.

7.3 Specific end use(s) For use in the Magnetic Particle Inspection Process (BS EN

ISO 9934-2). Dilution rate 50:1 with a suitable

hydrocarbon carrier.

Store locked up.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

8.1 **Control parameters** 

8.1.1 **Occupational Exposure Limits** 

SUBSTANCE	CAS No.	LTEL (8 hr	LTEL (8 hr	STEL	STEL	Note
		TWA ppm)	TWA mg/m³)	(ppm)	(mg/m³)	
Distillates (petroleum),	64742-47-8	150	1200	-	-	WEL (Reciprocal
hydrotreated light;						Calculation
Kerosine — unspecified						Method)

WEL: Workplace Exposure Limit (UK HSE EH40)

**Biological limit value** 8.1.2 Not established.

8.1.3 **PNECs and DNELs** Not established.

8.2 **Exposure controls** 

Appropriate engineering controls 8.2.1

Personal protection equipment 8.2.2 Eye/face protection

Provide adequate ventilation.

Impervious gloves (EN 374).

Wear protective eye glasses for protection against liquid

splashes.

Skin protection (Hand protection/ Other) Wear suitable gloves if prolonged skin contact is likely.

Respiratory protection Not normally required.

Thermal hazards

Handling of larger amounts: A suitable mask with filter type A (EN14387 or EN405) may be appropriate. Use a

respirator/filter with at least: PF10: 10 x Protection Factor.

Not applicable.

Revision: 2.1 Page: 4/8 Date: 19/02/2020



8.2.3 Environmental Exposure Controls

Do not allow to enter drains, sewers or watercourses.

### 9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical

properties

Appearance Liquid.

Colour Green (Shaken).
Odour Paraffinic.
Odour Threshold (ppm) Not available.
pH (Value) Not available.
Melting Point (°C) Not available.
Boiling Point (°C) 198°C
Flash Point (°C) >70°C

Evaporation rate Not applicable. Non-flammable. Flammability Explosive limit ranges 0.6 - 7 Vol-%Not available. Vapour Pressure (mm Hg) Vapour Density (Air=1) Not available. Bulk Density (g/ml) @ 15°C ~0.79 Solubility (Water) Immiscible. Solubility (Other) Not available. Partition Coefficient (n-Octanol/water) Not available. >200°C Auto Ignition Temperature (°C) Not available. Decomposition Temperature (°C) Kinematic Viscosity @ 40°C <3cSt

Explosive properties Not available.

Oxidising properties No information available.

9.2 Other information None.

## 10. SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity
 10.2 Chemical stability
 10.3 Possibility of hazardous reactions
 10.4 Conditions to avoid
 10.5 Stable under normal conditions.
 10.6 Stable under normal conditions.
 10.7 Heat and direct sunlight.

10.5 Incompatible materials Strong oxidising agents, Natural rubber, Butyl rubber,

Polystyrene.

10.6 Hazardous Decomposition Product(s) Carbon monoxide, Carbon dioxide.

### 11. SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

11.1.1 Mixtures

**Acute toxicity** 

Ingestion Low oral toxicity.

Distillates (petroleum), hydrotreated light; Kerosine —

unspecified: LD50 (rat) : >15000mg/kg

Inhalation Low acute toxicity.

Distillates (petroleum), hydrotreated light; Kerosine — unspecified: LC50 (rat) 4hour(s): >4951mg/m³

Revision: 2.1 Page: 5/8 Date: 19/02/2020



Skin Contact Low acute toxicity.

Distillates (petroleum), hydrotreated light; Kerosine —

unspecified: LD50 (rabbit): >2000mg/kg

Eye Contact Low acute toxicity.

Irritation Repeated exposure may cause skin dryness or cracking.

Corrosivity Not classified.

Sensitisation Not expected to be a skin or respiratory sensitiser.

Repeated dose toxicity None anticipated.

Carcinogenicity No evidence of carcinogenicity.

Mutagenicity There is no evidence of mutagenic potential.

Toxicity for reproduction None anticipated.

Aspiration hazard Asp. Tox. 1: May be fatal if swallowed and enters airways.

None.

Aspiration into the lungs may cause chemical pneumonitis,

which can be fatal.

11.2 Other information

## 12. SECTION 12: ECOLOGICAL INFORMATION

**12.1 Toxicity** Low toxicity to aquatic organisms.

12.2 Persistence and degradability The product is not biodegradable. There is evidence of

photodegradation in air. The product is unlikely to persist in

the environment.

**12.3** Bioaccumulative potential The product has potential for bioaccumulation.

Distillates (petroleum), hydrotreated light; Kerosine —

unspecified: BCF = 130-159

**12.4 Mobility in soil** Immiscible with water. The product is predicted to have low

mobility in soil. The product is volatile and will partition into the atmosphere. Higher molecular weight hydrocarbons: The

substance may adsorb onto soils and sediments.

12.5 Results of PBT and vPvB assessment Not classified as PBT or vPvB.

12.6 Other adverse effects None.

### 13. SECTION 13: DISPOSAL CONSIDERATIONS

**13.1** Waste treatment methods Dispose of contents/container to: Licensed recycler.

Refer to manufacturer for information on recovery/recycling.

Do NOT landfill.

13.2 Additional Information Disposal should be in accordance with local, state or national

legislation.

### 14. SECTION 14: TRANSPORT INFORMATION

Not classified as dangerous for transport.

14.1 **UN** number Not applicable. 14.2 **UN Proper Shipping Name** Not applicable. Not applicable. 14.3 Transport hazard class(es) 14.4 Packing Group Not applicable. Not applicable. 14.5 Environmental hazards 14.6 Special precautions for user Not applicable. 14.7 Transport in bulk according to Annex II of Not applicable. MARPOL73/78 and the IBC Code

Revision: 2.1 Page: 6/8 Date: 19/02/2020



## 15. SECTION 15: REGULATORY INFORMATION

Safety, health and environmental

regulations/legislation specific for the substance

or mixture

15.1.1 EU regulations

Authorisations and/or restrictions on use

None known. None known.

15.1.2 National regulations

15.2 **Chemical Safety Assessment**  Not available.

## 16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

#### **LEGEND**

LTEL Long Term Exposure Limit Short Term Exposure Limit STEL Derived No Effect Level **DNEL** 

PNEC Predicted No Effect Concentration PBT Persistent, Bioaccumulative and Toxic vPvB very Persistent and very Bioaccumulative

Asp. Tox. 1 Aspiration hazard Category 1

Harmful Xn

#### **Risk Phrases and Safety Phrases**

Flammable. R65

R66 Repeated exposure may cause skin dryness or cracking.

S2 Keep out of the reach of children.

S23 Do not breathe vapour. S24 Avoid contact with skin.

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or

label.

## Hazard statement(s)

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

## Hazard pictogram(s) and Hazard Symbol

GHS08

Xn



#### **Disclaimers**

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Johnson and Allen Ltd. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Johnson and Allen Ltd. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Revision: 2.1 Page: 7/8 Date: 19/02/2020



Annex to the extended Safety Data Sheet (eSDS)

No information available.

Revision: 2.1 Page: 8/8 Date: 19/02/2020